# **MSDS**

The attached MSDS applies to the following products:

**VENDOR:** RECTORSEAL

STOCK# MFG#/DESCRIPTION

G89-799 81875 AIRLOCK 1 GAL

## MATERIAL SAFETY DATA SHEET- AIR-LOCKO 181

MSDS0213 Ver. No.1 Ver. Date February 11, 1999

#### SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Air-Lock® 181
CHEMICAL FAMILY: Organic/Inorganic

**USE:** Duct Sealant

MANUFACTURE / SUPPLIER
The RectorSeal Corporation
2601 Spenwick

Houston, Texas 77055 USA

**EMERGENCY TELEPHONE NUMBERS:** 

Chemtrec 24 hours: (800) 424-9300 The RectorSeal Corporation: (713) 263-8001

The RectorSeal Corporation: (713) 263-8001

NON EMERGENCY TELEPHONE NUMBERS:

Nο

Technical Service: (800) 231-3345

UEL: N/A

#### **SECTION 2 COMPOSITION / INFORMATION ON INGREDIENTS**

APPROX

HAZARDOUS COMPONENTS CAS NO. % OSHA PEL ACGIH TLV OTHER LIMITS HMIS NFPA

None as defined by OSHA Hazard Communication Standard 29 CFR 1910.1200

SECTION 3 HAZARDS IDENTIFICATION

SUMMARY OF ACUTE HAZARDS None known

ROUTE OF EXPOSURE SIGNS AND SYMPTOMS PRIMARY
ROUTE OF EXPOSURE SIGNS AND SYMPTOMS ROUTE(S)

INHALATION: N/A

N/A

 EYE CONTACT:
 Contact may cause eye irritation.
 Yes

 SKIN CONTACT:
 May cause skin irritation.
 Yes

 INGESTION:
 Possible irritation to mucous membranes of the mouth, throat, and stomach.
 No

SUMMARY OF CHRONIC HAZARDS: None known

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/D

SECTION 4 FIRST AID MEASURES

INHALATION: N/A

**EYE CONTACT:** Flush eyes with plenty of water. Call a physician if irritation persists. **SKIN CONTACT:** Wash with soap and water. If irritation occurs, seek medical attention.

**INGESTION:** If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give

anything by mouth to an unconscious person.

**SECTION 5 FIRE FIGHTING MEASURES** 

FLASH POINT: None FLAMMABILITY LIMITS: LEL: N/A

**EXTINGUISHING MEDIA:** Foam, dry chemical, carbon dioxide or water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained full face piece breathing apparatus and other protective clothing. Toxic

decomposition products possible (see Section 10).

UNUSUAL FIRE AND EXPLOSION HAZARDS: Heat may build up and rupture closed containers.

SECTION 6 ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wipe up spills to prevent footing hazard. Avoid flushing into sewers, drains, waterways and soil. Wear protective clothing during clean up.

### **SECTION 7 STORAGE AND HANDLING**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Keep container closed when not in use. To prevent freezing and possible rupture of container, do not store below 40°F(4°C).

OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues and vapors; treat as if full and observe all products precautions. Do not reuse empty containers. KEEP OUT OF REACH OF CHILDREN.

#### SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE): Normally none required.

VENTILATION - LOCAL EXHAUST: Acceptable Special: N/A
MECHANICAL (GENERAL): Acceptable OTHER: N/A

PROTECTIVE GLOVES: Wear non-permeable gloves. EYE PROTECTION: Goggles (ANSI Z-87.1 or equivalent)

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended.

**WORK/HYGIENIC PRACTICES:** Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

### MATERIAL SAFETY DATA SHEET- AIR-LOCKO 181

MSDS0213 Ver. No.1

Ver. Date February 11, 1999

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

SPECIFIC GRAVITY ( $H_20 = 1$ ): 1.60 **BOILING POINT:** 212°F (100°C)

VAPOR PRESSURE (mm Hg): 17 @ 68°F (20°C) MELTING POINT: N/A

VAPOR DENSITY (AIR = 1): N/A **EVAPORATION RATE (ETHYL ACETATE = 1):** 1 **SOLUBILITY IN WATER:** Soluble APPEARANCE/ODOR: White Paste/Mild Odor

**SECTION 10 STABILITY AND REACTIVITY** 

STABILITY: Stable

**CONDITIONS TO AVOID: None** 

INCOMPATIBILITY (MATERIALS TO AVOID): Sulfuric acid or alkali metals.

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO , Hydrogen chloride evolved above 600°F (315°C).

HAZARDOUS POLYMERIZATION: Will not occur.

**SECTION 11 TOXICOLOGY INFORMATION** 

**CARCINOGENICITY:** NTP: No IARC MONOGRAPHS: No OSHA REGULATED: No

**SUBSTANCE** CAS NO. LD50 LC50 N/A N/A N/A N/A

**SECTION 12 ECOLOGICAL INFORMATION** 

**FOOD CHAIN** 

**SUBSTANCE CON POTENTIAL** WATERFOWL TOXICITY BOD **AQUATIC TOXICITY** 

N/A

SECTION 13 DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of clean up materials in accordance with all local, state and federal regulations.

SECTION 14 TRANSPORTATION INFORMATION

**DOT:** Non-Regulated

OCEAN (IMDG): Non-Regulated AIR (IATA): Non-Regulated WHMIS (CANADA): Non-Regulated

SECTION 15 REGULATORY INFORMATION

CERCLA\_RQ **TSCA INVENTORY RCRA CODE SUBSTANCE SARA\_313** 

N/A All ingredients listed. N/A

**SECTION 16 OTHER INFORMATION** 

This document is prepared pursuant to the OSHA Hazardous Communication Standard (29 CFR 1910.1200). The information herein is given in good

faith, but no warranty, express or implied is made. Consult The RectorSeal Corporation for further information: (713) 263-8001.