

Vent-Free Gas Heaters

 **WILLIAMS**

Two attractive inexpensive solutions
for assured, on-command home heating.
Power heating in a compact package!

Get quick efficient warmth without the need for
venting or electricity. Relax in comfort created by
these 99.9% efficient heaters with low-fuel
consumption and quiet operation.

For additional savings,
install one of our optional blowers.



Blue-Flame

6,000 to 30,000 Btu/hr.

Blue-Flame Heaters distribute heat evenly
throughout your room, quickly warming the
surrounding air. This heater's cheerful blue-flame
is visible from behind the safety glass.



Infrared

6,000 to 30,000 Btu/hr.

Infrared heaters provide direct radiant
heat, quickly warming people and objects
in the room. Ceramic plaques behind the
grille gives this heater its' warm glow.

Design Features

- ✓ No electricity required
- ✓ Economical: 99.9% efficient
- ✓ Push button "Matchless" igniter
- ✓ Temperature and safety controls
- ✓ No outside duct or chimney needed
- ✓ Space saving design without sacrificing beauty
- ✓ Easy to install - placement is virtually unlimited
- ✓ Operational controls available with manual (1 to 3) or automatic (variable), top-mounted thermostat settings
- ✓ Available in natural or propane gas. Selected models are equipped with the "Fuel Exchange System" that lets you use either natural or propane gas
- ✓ O.D.S. (Oxygen Depletion Sensor) with automatic shut-off
- ✓ Contemporary finish to match any décor

Vent-Free Gas Heaters

Model	Fuel Type	Btu/hr. Input	Certified	Dimensions			Thermostat	Shipping Weight (lbs.)
				Width	Depth	Height		

BLUE FLAME MODELS

0656542.9	Natural	6,000	CSA	13¾	5½	19¾	Manual	15
0656541.9	Propane	6,000	CSA	13¾	5½	19¾	Manual	15
1056512.9	Natural	10,000	CSA	13¾	5½	19¾	Auto	15
1056511.9	Propane	10,000	CSA	13¾	5½	19¾	Auto	15
1056542.9	Natural	10,000	CSA	13¾	5½	19¾	Manual	15
1056541.9	Propane	10,000	CSA	13¾	5½	19¾	Manual	15
1086511.9	Propane	5,000 - 10,000	PFS	13¾	8	21¾	Auto	16
1096513.9	Natural/Propane *	10,000	PFS	14¾	6¾	19¾	Auto	18
1096543.9	Natural/Propane *	10,000	PFS	14¾	6¾	19¾	Manual	17
2056512.9	Natural	20,000	CSA	18¾	7¾	24¾	Auto	27
2056511.9	Propane	20,000	CSA	18¾	7¾	24¾	Auto	27
2096513.9	Natural/Propane *	20,000	PFS	19¾	8	23¾	Auto	27
3056512.9	Natural	30,000	CSA	26¾	7¾	24¾	Auto	32
3056511.9	Propane	30,000	CSA	26¾	7¾	24¾	Auto	32
3086511.9	Propane	30,000	PFS	24½	8	25½	Auto	33
3096513.9	Natural/Propane *	30,000	PFS	26¾	8	23¾	Auto	34

INFRARED MODELS

0686541	Propane	6,000	PFS	13¾	8	21¾	Manual	18
0696541	Propane	6,000	CSA	14¾	6¾	19¾	Manual	15
1096513	Natural/Propane *	10,000 - Propane 12,000 - Natural	PFS	14¾	7¾	19¾	Auto	19
1096541	Propane	5,500 - 10,000	CSA	14¾	6¾	19¾	Manual	16
1286513 *	Natural/Propane *	12,000	CSA	16½	7¾	25	Auto	25
1286543 *	Natural/Propane *	12,000	CSA	16½	7¾	25	Manual	25
1886542 *	Natural	6,600 - 12,000 - 18,000	PFS	18¾	8	24½	Manual	26
2086513 *	Natural/Propane *	18,000	CSA	21¾	10¾	26¾	Auto	27½
2096513	Natural/Propane *	20,000	PFS	19¾	8	23¾	Auto	35
2686541 *	Propane	6,600 - 11,000 - 26,000	PFS	24½	8	25½	Manual	34
3086513 *	Natural/Propane *	30,000	CSA	28¾	10¾	26¾	Auto	36

* Floor Stand Included

Recommended Minimum Clearances

Blue Flame	A	B	C	Infrared	A	B	C
0656542.9	36"	6"	6"	0686541	36"	6"	3"
0656541.9	36"	6"	6"	0696541	36"	6"	2"
1056512.9	36"	6"	6"	1096513	36"	8"	2"
1056511.9	36"	6"	6"	1096541	36"	8"	2"
1056542.9	36"	6"	6"	1286513	36"	8"	3"
1056541.9	36"	6"	6"	1286543	36"	8"	3"
1086511.9	36"	6"	3"	1886542	36"	10"	2"
1096513.9	36"	8"	2"	2086513	36"	10"	3"
1096543.9	36"	8"	2"	2096513	36"	10"	2"
2056512.9	36"	6"	6"	2686541	36"	10"	2"
2056511.9	36"	6"	6"	3086513	36"	10"	3"
2096513.9	36"	8"	2"				
3056512.9	36"	6"	6"				
3056511.9	36"	6"	6"				
3086511.9	36"	10"	2"				
3096513.9	36"	8"	2"				

- A. Distance from top of appliance to ceiling or other obstruction
B. Distance from the side
C. Distance from the top surface of carpeting, tile or other combustible material

Accessories


Model	Description	Application	Shipping Weight
2205	Blower Accessory, Automatic	2056511.9, 2056512.9, 3056511.9, 3056512.9	2
2206	Blower Accessory, Manual	2056511.9, 2056512.9, 3056511.9, 3056512.9	2
2286	Blower Accessory, Automatic	1886542, 2686541, 3086511.9	2
2289	Blower Accessory, Automatic	1286543, 1286513, 2086513, 3086513	2
2295	Blower Accessory, Automatic	2096513, 2096513.9, 3096513.9	2
4288	Floor Base	2056511.9, 2056512.9, 3056511.9, 3056512.9	4
4291	Floor Base	1096513.9, 1096543.9, 1096513, 1096541, 0696541	4
4292	Floor Base	2096513.9, 3096513.9, 2096513	4

Great During Power Outrages



No Electricity Required

*Fuel Exchange System



The Fuel Exchange System allows you to convert from Propane to Natural Gas or Natural to Propane Gas without a gas conversion kit.

Important

- Read owner's manual before using/installing.
- Not for use in recreational vehicles.
- Photographs are representative only.
- Check local codes and ordinances for permitted uses.
- Consult installation manual for clearances prior to installation.
- We reserve the right to amend product specifications without notice.
- Installation and servicing recommended by a qualified service person.
- Use with adequate air (ventilation) only. Refer to owner's manual for details.
- Operating heater at elevations above 4,500 feet could result in nuisance outages.
- Specify propane or natural gas when ordering. Models designated for use with dedicated natural or propane gas are not intended for conversion between fuel types.
- Please read the warranty for any limitations or disclaimers. All parts carry a one-year limited warranty.



Scan for more information on Williams Comfort Products



250 Laurel Street • Colton, California 92324 USA
(909) 825-0993 • Fax: (909) 370-0581 or (909) 824-8009
Consumer Line: (888) 256-6465
Website: e-wfc.com

facebook.com/WilliamsProducts • linkedin.com/company/williams
youtube.com/user/WilliamsProduct • instagram.com/williamsproducts
twitter.com/WilliamsProduct