

Features:

Six Sizes Available

- PI-T50 18 to 50 MBH Input Modulation
- PI-T80 27 to 80 MBH Input Modulation
- PI-80 27 to 80 MBH Input Modulation
- PI-140 46 to 140 MBH Input Modulation
- PI-199 66 to 199 MBH Input Modulation
- PI-399 133 to 399 MBH Input Modulation

New P825 Control Board Features

- Outdoor Reset
- Domestic Hot Water Priority
- Improved Troubleshooting with LED status display module
- Service Mode for manual control of firing rate
- Optional Interface Module for External Sequencing Controls
- Available Software to display status information or fault history from your PC

Fully Modulating Burner for Maximum Efficiency

• 95.1% AFUE - Energy Star[®] Efficient*

Natural or LP Gas

Direct Vent

- Sealed Combustion
- No Chimney Required Horizontal or Vertical Venting
- Uses Standard Schedule 40 PVC Plastic Pipe for Venting
- Concentric PVC or Stainless Steel Vent Kits Available

Compact, Light-Weight Design

- Installation Flexibility
- Zero Clearance to Combustibles
- Lightweight Design (65 to 252 lbs.) & Small Footprint

Stainless Steel Construction

• *High Grade Stainless Steel Burner and Heat Exchanger*

Safe Operation

- Venturi Gas Valves
- State-of-the-Art Control Board
- Spark Ignition

Quiet Operation

• As Quiet as Most Home Appliances

*On boilers firing below 300,000 Btu/hr only.

Environmentally Friendly

Low Emissions



As an ENERGY STAR[®] Partner, PB Heat, LLC has determined that this product meets the ENERGY STAR guidelines for energy efficiency.

Standard Equipment:

- Venturi Gas Valve
- Burner Fan
- High Limit Temperature Control
- 30 PSI Safety Relief Valve
- Combination Temperature-Pressure Gauge
- PVC Screened Air Intake Terminal and Exhaust Terminal
- Outdoor Sensor

Optional Equipment:

- Stainless Steel Vent Termination Kit
- Concentric PVC Vent Termination Kit
- Floor or Wall Mounted Steel Boiler Stand
- Domestic Water Tank Sensor
- 50 PSIG Relief Valve (Excluding Models T50 & T80)

We are pleased to offer one of the most comprehensive warranty programs in the industry. The Peerless Pinnacle stainless steel boiler carries a full one-year warranty on the entire boiler and a three-year warranty on the blower assembly. We will also purchase an additional warranty that covers labor for replacing warranted parts from the 31st day through the first year after installation, provided the warranty registration card is returned. In addition, we offer a limited, pro-rated, 12-year warranty on the heat exchanger of the Pinnacle boiler. Five and ten-year extended warranties on parts and labor may also be purchased. This summary is not a specific warranty. Please consult us for complete warranty information.

A Complete

Warranty

Program!



PeerlessBoilers.com



FAB-PI R8 (12/08-3M) Printed in U.S.A