



THE RINNAI VALUE SERIES EXCEPTIONAL COMFORT. REMARKABLE CONVENIENCE. EXTRAORDINARY VALUE.

RINNAI VALUE SERIES RESIDENTIAL TANKLESS WATER HEATER

Rinnai ... The Affordable Way to Heat Water

Delight in the comfort and convenience of continuous hot water – and in the value of a tankless water heater that offers so much indulgence so affordably. Rinnai's Value Series Tankless Water Heater efficiently delivers up to 5.3 gallons per minute (GPM) of hot water – perfect for your one- or two-bathroom home.

This easy-to-install, compact package lets you enjoy all the benefits of Rinnai tankless water heating. You'll experience clean, endless hot water, while saving energy and precious floor space in your home. Plus, you'll get the reliability and durability that only Rinnai can offer.

You'll Appreciate Other Features and Benefits of the RV Series

- Available in interior (RV53i) or exterior (RV53e) models
- New RV53i Models are now certified for installation in manufactured (mobile) homes. Contact your Rinnai representative for details.
- Pre-set at 120°F (adjustable to 140°F by the installer)
- Integrated error code indicator
- Lightweight and compact
- Natural gas and propane models available
- Meets California and Texas NOx emission standards
- Energy Factor of .82 for both gas types
- 10-year warranty on heat exchanger (5 years on parts, 1 year on labor)
- Compatible with full line of Rinnai digital controllers
- Temperature range with controllers: 98°F 140°F
- ENERGY STAR® qualified models

Rinnai RV Series...The Perfect Combination of Comfort and Value

- **Never Run Out of Hot Water.** Enjoy continuous hot water delivered simultaneously to multiple plumbing and appliance demands. Water is always at a consistent temperature.
- **Lower Your Energy Costs.** Heat water only when you need it, and eliminate the expense of continually reheating water in a holding tank.
- Free Up Valuable Living Space. Gain as much as 16 square feet of living space in your home when you replace your tank-style water heater with a RV53.
- Perfect for New Homes or Remodeling. The direct-vent RV53i requires only
 a single roof or wall penetration, and the RV53e requires no additional venting
 components.
- **Enjoy Peace of Mind.** Rinnai offers one of the best warranties in the industry a full 10 years on the heat exchanger, five years on all other parts, and one year on labor.







RV53i

RINNAI VALUE SERIES: AFFORDABLE LUXURY FOR YOUR SMALLER HOME.





RV53i Interior model


Value Series Warranty

Warranty (some restrictions apply): Heat exchanger limited warranty 10 years residential; 3 years when used in certain recirculating systems; 10 years when used with a Rinnai hydronic furnace. All other parts: 5 years. *Labor: 1 year residential. For more warranty details, visit www.rinnai.us or call 1-800-621-9419.

WHOLE-HOUSE SIMULTANEOUS BATH-USE

| Model | Ground Water Temperature | |
|-------|--------------------------|-----------------------|
| RV53i | Summer Season — 70° F | Winter Season — 50° F |
| RV53e | | |

Customer has the option of using the following appliances instead of a shower: residential grade clothes wash machines or dishwashers. Shower heads assumed to be 2.5 GPM mixed flow rate or less. If custom shower fixtures i.e. body sprays, large rain heads, or tubs over 60 gallons in capacity are used, please contact Rinnai.



| 0 10 41 | DVCD'L DE LL | DV-0 | |
|----------------------|---|----------------------|--|
| Specifications | RV53i Interior Model | RV53e Exterior Model | |
| Dimensions | 14" W x 24" H x 9" D | 14"W x 21" H x 7" D | |
| Weight | 51 lbs. | 34 lbs. | |
| Ignition | Direct electronic | | |
| Hot Water Capacity | 0.6 to 5.3 GPM | 0.6 to 5.3 GPM | |
| Min/Max Gas Rate | NG: 15,000 – 150,000 | NG: 19,000 – 120,000 | |
| (BTU Input) | LP: 15,000 – 150,000 | LP: 20,200 - 120,000 | |
| Energy Factor | .82 for NG or LP | | |
| Gas Type | Natural Gas (NG) or Propane (LP) | | |
| Temperature Settings | 98°F - 120°F (factory default) or 140°F** | | |
| Status Monitor | Included | | |

^{**} Units come with a default maximum temperature of 120° F for increased safety and code compliance. An option to increase the max temp to 140° F is also be available. RV models require a controller to increase max temperature.

- MC-91-1S/W Digital Controller ("S" silver or "W" white available)
- RGB-20U Recess Box RV53e only (for flush-mounting on exterior wall)
- PC-25-W (RV53i) or PC-20-W (RV53e) Pipe Cover (for concealing plumbing and gas lines)
- REU-PVA-4 Pressure Activated Valves for manifolding 2 or more RV53e units.

Rinnai is continually updating and improving products; therefore, specifications are subject to change without prior notice. Local, state, provincial and federal codes must be adhered to prior to and upon installation.

FOR MORE INFORMATION ON RINNAI PRODUCTS

ADDITIONAL RINNAI LITERATURE AVAILABLE HYDRONIC

RESIDENTIAL TANKLESS

WATER HEATERS





DIRECT VENT

Rinnai America Corporation

103 International Drive Peachtree City, GA 30269

Toll Free 1-800-621-9419

Phone: 678-829-1700 • Fax: 678-364-8643 Visit our Website www.rinnai.us E-mail: marketing@rinnai.us













