

Aqua-Pure®

Spec # _____

Quantity _____

Models:

AP510

Full Flow Drinking Water System

Applications:

- Chlorine Taste & Odor
- Sediment / Rust
- Scale

At a Glance:

- Triple action filtering process to help provide better quality ice cubes, fresher tasting water, coffee and beverages
- 3/8" NPT inlet/outlet connections



AP510


Product Benefits:

- Designed with built-in shut-off valve offering fast and easy cartridge changes
- Premium depth filter for higher sediment removal efficiency and longer cartridge life
- Specially formulated high adsorption activated carbon media for long cartridge life and reduction of unwanted chlorine taste and odor
- Scale and corrosion inhibition system helps protect equipment and ice makers against scale build-up and the damaging effects of corrosion
- Manufactured from FDA CFR-21 compliant materials
- Complete installation manual is enclosed for easy reference and simple installation

Product Specifications:

Model No. (Part No.)	Inlet/ Outlet Size	Dimensions		Flow Rate	Capacity	Max. Water Temp.	Max. Water Pressure	Degree of Filtration	Std. Replacement Ctg. No.
		Height	Diameter						
AP510 (5592202)	3/8" NPT	11-3/8" (28.9 cm)	3-5/8" (9.2 cm)	2 gpm (7.6 lpm)	2,000 gallons (7,571 liters)	100°F (37.8°C)	125 psi (862 kPa)	5 Micron Nominal	AP517 (AP51701)


Aqua-Pure®



AP510

Easy Installation:

CAUTION: Diagram shown is for reference purposes only. Read installation and operation manual prior to installing the unit.



Spec # _____

Quantity _____

Model Number _____

Part Number _____

Physical Specifications:

- 3/8" NPT inlet/outlet connection
- System is a single vessel design
- System is manufactured from FDA CFR-21 compliant materials
- System has a maximum operating pressure of 125 psi (862 kPa) and operating temperature of 100°F (37.8°C)
- System to be installed on primary kitchen or bath cold water line on existing faucet

Replacement Cartridge Options

Sediment Model	Nominal Micron Rating	Application			Flow Rate
		Sediment/ Rust	Chlorine Taste & Odor	Scale	
AP517	5	•	•	•	1.3 gpm (4.9 lpm)

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

CUNO Incorporated recommends regularly scheduled maintenance and replacement of the filter cartridge(s) in order for the product to perform as advertised/sold. **Change the filter cartridge at least every 6 months. Improper installation and maintenance may result in property damage due to water leakage.**

Limited Warranty:

CUNO Incorporated warrants this Product to be free from defects in material and workmanship for two (2) years from the date of purchase. This warranty does not cover failures resulting from abuse, misuse, alteration or damage not caused by CUNO or failure to follow installation and use instructions. If the Product is defective CUNO will replace the Product or refund your Product purchase price. CUNO will not be liable for any indirect, special, incidental, or consequential damages arising from the use of this Product. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation may not apply to you. To obtain warranty service, mail your request to Warranty Claims, CUNO Incorporated, 400 Research Parkway, Meriden, CT 06450. Proof of purchase (original sales receipt) must accompany the warranty claim, along with a complete description of the Product, model number and alleged defect. This warranty gives you specific legal rights and you may have other rights which vary from state to state, or country to country.

Distributed by:

CUNO and Aqua-Pure are trademarks of 3M Company used under license. NSF is a trademark of NSF International. © 2007 3M Company. All rights reserved. LITAP621 0907



Visit www.nsf.org for the claims associated with products that are NSF listed.



CUNO Incorporated
400 Research Parkway
Meriden, CT 06450 U.S.A.
Toll Free: 1.800.222.7880
Worldwide: 203.237.5541
Fax: 203.238.8701
www.aquapure.com • www.cuno.com