### **Vented Hearth Heaters**

Model Number		Btu/hr	Btu/hr	Color	Efficiency Percentages		Dimensions			Vent	Center	Shipping
Natural	Propane	Input	Output	Color	Thermal	AFUE	Width	Depth	Height	Size	Vent to Floor	Weight (lbs.)
ENCLOSED FR	ONT MODELS											
2001622	2001621	20,000	16,000	Black	80.0	73.0	23"	11"	21½"	3"	17"	45
2001622.3	-	20,000	16,000	White	80.0	73.0	23"	11"	21½"	3"	17"	45
3501522	3501521	35,000	26,250	Black	75.0	68.0	25"	15%"	287/8"	4"	213/8"	74
* 3501922	3501921	35,000	26,250	Black	75.0	68.0	25"	15¾"	287/8"	4"	213/8"	83
5001522	5001521	50,000	34,500	Black	69.0	64.0	30"	16"	321/8"	4"	22¾"	103
* 5001922	5001921	50,000	34,500	Black	69.0	64.0	30"	16"	321/8"	4"	22¾"	112
6501522	6501521	65,000	50,400	Black	78.0	71.0	34"	195/8"	32%"	5"	24¾"	128
* 6501922	6501921	65,000	50,400	Black	78.0	71.0	34"	195/8"	321/8"	5"	24¾"	137
<b>GLASS FRONT</b>	"FIREPLACE LO	OOK" MODE	LS									
3502522	3502521	35,000	26,250	Black	75.0	68.0	25"	15%"	287/8"	4"	21%"	81
* 3502922	3502921	35,000	26,250	Black	75.0	68.0	25"	15%"	287/8"	4"	21%"	90
5002522	5002521	50,000	34,500	Black	69.0	64.0	30"	16"	321/8"	4"	22¾"	108
* 5002922	5002921	50,000	34,500	Black	69.0	64.0	30"	16"	321/8"	4"	22¾"	117
6502522	6502521	65,000	50,400	Black	78.0	71.0	34"	195/8"	321/8"	5"	24¾"	135
* 6502922	6502921	65,000	50,400	Black	78.0	71.0	34"	195/8"	32%"	5"	24¾"	144

All models have  $\frac{1}{2}$  gas connection • Equipped with blower • All models are rated for 4,500' elevation

### **Features**

- · Contemporary black or white, powder-coat, scratch-resistant finish to complement any décor.
- Equipped with a self-generating, millivolt thermostat that can be wall-mounted or cabinet-mounted.
- $\cdot$  35,000, 50,000 and 65,000 Btu/hr. models are available with a factory installed blower. Blower also available for field installation.



Great During Power Outages

### Accessories

### **Vent Collars**

Model	Description	Shipping Weight (lbs)		
9101	White for 3" vents	1		
9102	Black for 3" vents	1		
9104	Black for 4" vents	1		
9106	Black for 5" vents	1		

#### **Floorboards**

Model	Description	Weight	
4163	Black for 50,000 and 65,000 Btu/hr. Models	16	
4166	White for 20,000 Btu/hr. Models	10	
4167	Black for 20,000 and 35,000 Btu/hr. Models	10	

## Oversized Shipping

Weight (lbs	;)
16	
10	



#### **Blower**

A heavy-duty, quiet blower is available for larger rooms where faster heat circulation is desired.

150 CFM, 120V. **Model 2102**, shipping weight 9 lbs. Not for use on 20016 series

### Conversion Kits High-Altitude Models








250 West Laurel Street · Colton, California 92324 USA (909) 825-0993 · Fax: (909) 370-0581 or (909) 824-8009 Consumer Line: (888) 256-6465

Consumer Line: (888) 256-6465 Homeowner Assistance: (909) 426-0978 www.e-wfc.com

# Dimensions and Clearances

Although the vent pipe is not shown, this product must be vented to the outside.



MODEL	Α	В	С	D
200 Series	2"	22"	3"	24"
350, 500 & 650 Series	6"	57"	6"	24"

### Important

- Read owner's manual before using/installing.
- Photographs are representative only.
- Specify propane or natural gas when ordering.

  Check local codes and ordinances for permitted uses.
- Consult installation manual for clearances prior to installation.
- We reserve the right to amend product specifications without notice.
- Installation and servicing recommended by a qualified service person.
- Please read the warranty, for any limitations or disclaimers. Combustion chamber carries a ten-year limited warranty. All other parts carry a one-year limited warranty.
- Venting must comply with the "Venting and Chimney Requirements" section of installation manual.
- Massachusetts approval G3-0305-171

© 2008 Williams Furnace Co. Printed in U.S.A. All Rights Reserved L1013 5/08