

solution for fixed placement, solid surface applications when hanging a secondary drain pan and HVAC unit is not necessary. They are Made with Pride in the USA from our patented advanced polymer DexElar® material and feature a network of built-in risers, which are compatible with a wide variety of sizes of HVAC units.

Additional Goliath Value Series Secondary Drain Pans features include:

- Superior strength, durability and versatility when compared to other HVAC secondary drain pans made of traditional ABS plastics.
- Will not crack, split, or rust like a metal secondary drain pan.
- Can support 40% more weight than a traditional ABS plastic pan.
- Extreme temperature durability -20° F (-28°C) to 260° F (126.7°C) with a higher melting point and self extinguishing characteristics not found in competitors' secondary drain pans.
- DexElar® material is a safer material of choice than ABS plastic.

Goliath Value Series Secondary Drain Pans are compatible with our AG-4200 Condensate Management System water sensor and drain adapter as well as AG-GFR Vibration Isolators to quiet any noisy HVAC unit. (Sold separately)



Goliath Value Series Non-Hangable Secondary Drain Pans are to be used only for fixed placement HVAC installations and must be supported by a solid surface and are not to be hung in any application.







Goliath Value Series Secondary Drain Pans meet or exceed all international building codes and come with a 5 Year Limited Warranty.

GOLIATH VALUE SERIES							
PRODUCT	PAN SIZE	OUTER (MAX) DIMENSION			INSIDE (DRIP AREA) DIMENSION		
CODE #		"L" LENGTH	"W" WIDTH	"D" DEPTH	"I" length	"w" width	"d" depth
96214	30x50	50.50"	30.25"	4.00"	45.25"	22.75"	2.1"
96216	30x62	63.0"	30.375"	4.25"	56.875"	22.75"	2.1"
96218	30x66	66.50"	30.25"	4.00"	64.00"	22.75"	2.1"

All pans meet or exceed all international building codes and come with a 5 Year Limited Warranty. US Patent 7,900,795



