# **Vent-Free Gas Heaters**



Two attractive inexpensive solutions for assured, on-command home heating. Power heating in a compact package!

Get quick efficient warmth without the need for venting or electricity. Relax in comfort created by these 99.9% efficient heaters with low-fuel consumption and quiet operation.

For additional savings, install one of our optional blowers.



Blue-Flame 6,000 to 30,000 Btu/hr.

Blue-Flame Heaters distribute heat evenly throughout your room, quickly warming the surrounding air. This heater's cheerful blue-flame is visible from behind the safety glass.



## Infrared 6,000 to 30,000 Btu/hr.

Infrared heaters provide direct radiant heat, quickly warming people and objects in the room. Ceramic plaques behind the grille gives this heater its' warm glow.



**Great during power outages!** 

## **Design Features**

- No electricity required
- ▼ Economical: 99.9% efficient
- ✓ Push button "Matchless" igniter
- Temperature and safety controls
- ✓ No outside duct or chimney needed
- Space saving design without sacrificing beauty
- Easy to install placement is virtually unlimited
- Operational controls available with manual (1 to 3) or automatic (variable), top-mounted thermostat settings
- Available in natural or propane gas. Selected models are equipped with the "Fuel Exchange System" that lets you use either natural or propane gas
- ✓ O.D.S. (Oxygen Depletion Sensor) with automatic shut-off
- Contemporary finish to match any décor



The Fuel Exchange System allows you to convert from Propane to Natural gas or Natural to Propane Gas without a gas conversion kit.

## **Vent-Free Gas Heaters**

| Model Number           |                 | Nominal       | Contification | Dimensions     |       |        | <b>71</b>  | Shipping |  |  |  |  |
|------------------------|-----------------|---------------|---------------|----------------|-------|--------|------------|----------|--|--|--|--|
| Natural                | Propane         | Btu/hr. Input | Certification | Width          | Depth | Height | Thermostat | Weight   |  |  |  |  |
| BLUE-FLAME MODELS      |                 |               |               |                |       |        |            |          |  |  |  |  |
| 0656542.9              | 0656541.9       | 6,000         | CSA           | 13¾            | 5½    | 191/8  | No         | 15       |  |  |  |  |
| 0696542.9              | 0696541.9       | 6,000         | PFS           | 141/8          | 63/8  | 191/8  | No         | 15       |  |  |  |  |
| 1056512.9              | 1056511.9       | 10,000        | CSA           | 13¾            | 5½    | 191/8  | Yes        | 15       |  |  |  |  |
| 1056542.9              | 1056541.9       | 10,000        | CSA           | 13¾            | 5½    | 191/8  | No         | 15       |  |  |  |  |
| 1096513.9              |                 | 10,000        | PFS           | 141/8          | 63/8  | 191/8  | Yes        | 18       |  |  |  |  |
| 1096543.9              |                 | 10,000        | PFS           | 141/8          | 63/8  | 191/8  | No         | 17       |  |  |  |  |
| 2056512.9              | 2056511.9       | 20,000        | CSA           | 181/8          | 71/8  | 25     | Yes        | 27       |  |  |  |  |
| 2096513.9              |                 | 20,000        | PFS           | 191⁄4          | 8     | 231/2  | Yes        | 27       |  |  |  |  |
| 3056512.9              | 3056511.9       | 30,000        | CSA           | $26^{3}/_{16}$ | 71/8  | 25     | Yes        | 32       |  |  |  |  |
|                        | 3086511.9       | 30,000        | PFS           | 24½            | 8     | 25½    | Yes        | 33       |  |  |  |  |
| 3096513.9              |                 | 30,000        | PFS           | 265/8          | 8     | 23½    | Yes        | 34       |  |  |  |  |
| INFRARED PLAQUE MODELS |                 |               |               |                |       |        |            |          |  |  |  |  |
| 0696542                | 0696541         | 6,000         | CSA           | 141/8          | 63/8  | 191/8  | No         | 15       |  |  |  |  |
| 1096513                |                 | 10,000        | CSA           | 141/8          | 63/8  | 191/8  | Yes        | 19       |  |  |  |  |
| 2096513                |                 | 20,000        | CSA           | 191⁄4          | 8     | 23½    | Yes        | 35       |  |  |  |  |
| 3096513                |                 | 30,000        | CSA           | 265/8          | 8     | 23½    | Yes        | 38       |  |  |  |  |
| 3096542                | 3096542 3096541 |               | CSA           | 265/8          | 8     | 231/2  | No         | 38       |  |  |  |  |

### **ACCESSORIES**

| Model<br>Number | Description   |
|-----------------|---|
| 2205            | Blower Accessory - Automatic for 2056511.9, 2056512.9, 3056511.9 and 3056512.9      |
| 2206            | Blower Accessory - Manual for 2056511.9, 2056512.9, 3056511.9 and 3056512.9         |
| 2295            | Blower Accessory for 2096513, 2096513.9, 3096513, 3096513.9, 3096541, 3096542       |
| 4287            | Floor Base for 2056511.9, 2056512.9   |
| 4288            | Floor Base for 3056511.9, 3056512.9   |
| 4291            | Base Feet for 0696541, 0696542, 0696541.9, 0696542.9, 1096513, 1096513.9, 1096543.9 |
| 4292            | Base Feet for 2096513, 2096513.9, 3096513, 3096513.9, 3096541, 3096542              |

#### **Recommended Minimum Clearances**

| Blue-Flame | Α   | В   | C  | Infrared   | Α   | В   | C  |
|------------|-----|-----|----|------------|-----|-----|----|
| 065 Series | 36" | 6"  | 6" | 069 Series | 36" | 6"  | 2" |
| 105 Series | 36" | 6"  | 6" | 109 Series | 36" | 8"  | 2" |
| 109 Series | 36" | 8"  | 2" | 209 Series | 36" | 10" | 2" |
| 205 Series | 36" | 6"  | 6" | 309 Series | 36" | 10" | 3" |
| 209 Series | 36" | 8"  | 2" |            |     |     |    |
| 305 Series | 36" | 6"  | 6" |            |     |     |    |
| 308 Series | 36" | 10" | 2" |            |     |     |    |
| 309 Series | 36" | 8"  | 2" |            |     |     |    |

- A. Distance from top of appliance to ceiling or other obstruction.
- B. Distance from the side.
- C. Distance from the top surface of carpeting, tile or other combustible material.

#### Important

- Read owner's manual before using/installing.
- Not for use in recreational vehicles.
- · Photographs are representative only.
- Check local codes and ordinances for permitted uses.
  Consult installation manual for clearances prior to installation.
- · We reserve the right to amend product specifications without notice.
- Installation and servicing recommended by a qualified service person.
- Use with adequate air (ventilation) only. Refer to owner's manual for details.
- Operating heater at elevations above 4,500 feet could result in nuisance outages.
- Specify propane or natural gas when ordering. Models designated for use with dedicated natural or propane gas are not intended for conversion between fuel types.
- Please read the warranty for any limitations or disclaimers. All parts carry a oneyear limited warranty







