



NEW!

Rinnai®
MC502RC

WIRELESS REMOTE CONTROLLER FOR TANKLESS WATER HEATERS

FOR RESIDENTIAL APPLICATIONS

ANOTHER REVOLUTION IN HOT WATER: WIRELESS PERFORMANCE

Just as Rinnai changed the definition of water heaters, it now changes how you use them with radio frequency-based wireless control. The Wireless Remote Controller stays in contact with the water heater unit via an R/F signal, the first of its kind in the water heater industry. Perfect for remodels or retrofits, users can now enjoy the flexibility and control of remote operation without having to rewire the house.

COMPATIBILITY — WIRELESS PERFORMANCE

The new wireless controller is completely compatible with Rinnai tankless water heaters currently shipping with MC-91 controllers and can be used in conjunction with other Rinnai controllers. See table for possible combinations.

OPTIONS	RC Model #	RC Model #	RC Model #	RC Model #
OPTION 1	MC-91	MC-502	———	———
OPTION 2	MC-91	MC-502	MC-502	———
OPTION 3	MC-91	MC-502	MC-502	MC-502
OPTION 4	MC-502	MC-502	MC-502	MC-502
OPTION 5	MC-100	BC-100	BC-100	MC-502
OPTION 6	MC-100	BC-100	MC-502	MC-502
OPTION 7	MC-502	———	———	———

CONVENIENCE AND FLEXIBILITY

- Set to adjust water temperature at any fixture in the home
- Automatically communicates with water heater transceiver
- Water heater responds to remote inputs/temperature changes
- Comes with cradle for neat and secure storage
- Safe for use in showers (must be placed in cradle)
- Range is up to 65 feet (20m); 800 MHz signal with 2 channels
- Low consumption extends battery life up to 1 year (typical use)
- Uses 4 AA batteries




THE RINNAI ADVANTAGE GUARANTEE

- Warranty: 1 year on all parts for standard installation

BASIC AND ADVANCED FEATURES

- Displays diagnostic codes
- In use indicator
- Priority indicator
- Out of range indicator
- Four levels of communication/signal strength



NOTE: The wireless controller is designed to be used with the cradle in the shower, otherwise water may leak inside the unit.

MC-502RC



SPECIFICATIONS

Dimensions (Wireless Remote)	1.16" D x 4.33" W x 5.90" H
Dimensions (Transceiver)	1.38" D x 2.28" W x 6.57" H
Setpoint Temperature (Without Remote)	Factory Setting - 120°F (Residential)
Temperature Range	98° - 140° F (Residential)

MC-502RC PACKAGED WITH THE FOLLOWING



Transceiver
MC-205RC-1-US-M



Wireless Remote
MC-205RC-1-US-S



Remote Cradle

Rinnai is continually updating and improving products; therefore, specifications are subject to change without prior notice. Local, state, provincial and federal codes must be adhered to prior to installation.

CONTACT YOUR LOCAL AUTHORIZED DEALER

Rinnai Corporation

103 International Drive
Peachtree City, GA 30269

Toll Free 1-800-621-9419

Phone: 678-829-1700

Fax: 678-364-8643

Visit Our Web sites www.rinnai.us • www.foreverhotwater.com

E-mail: marketing@rinnai.us

Rinnai®

