

ELECTRIC BASEBOARD - STEEL ELEMENT CONVECTION HEATERS



- Available in white or ivory with steel heating element and aluminum fins
- Painted 22ga. steel front with 20 ga. junction boxes located on each end of the heater - junction boxes contain quick connect cable clamps and 6" ground lead wires
- Over-temperature thermal limit extends entire length of heated area
- A full length wireway provided along the back of the heater
 - optional wireway covers are available
- Heater can be mounted to the wall by using the key hole knockouts every 4" at the back of the heater
- Optional In-Built thermostats field installed in the junction box
- HEIGHT - 6" DEPTH - 2 1/2"

UPC 686334	IVORY MODEL	UPC 686334	WHITE MODEL	WATTS	BTU's	VOLTS	AMPS	HEATER LENGTH (IN)	WT. (LBS.)	LIST
104302	E2903-024S	104999	E2903-024SW	375	1275	120	3.1	24	5	55
104319	F2903-024S	105002	F2903-024SW	375	1275	208	1.8			
104326	H2903-024S	105019	H2903-024SW	375 / 281	1275 / 955	240 / 208	1.6/1.4			
104333	G2903-024S	105026	G2903-024SW	375 / 281	1275 / 955	277 / 240	1.6/1.2			
104340	E2905-028S	105033	E2905-028SW	500	1706	120	4.2	28	6	57
104357	F2905-028S	105040	F2905-028SW	500	1706	208	2.4			
104364	H2905-028S	105057	H2905-028SW	500 / 375	1706 / 1275	240 / 208	2.1/1.8			
104371	G2905-028S	105064	G2905-028SW	500 / 375	1706 / 1275	277 / 240	1.8/1.6			
104388	E2906-036S	105071	E2906-036SW	600	2040	120	5.0	36	7	64
104395	F2906-036S	105088	F2906-036SW	600	2040	208	2.9			
104401	H2906-036S	105095	H2906-036SW	600 / 450	2040 / 1530	240 / 208	2.5/2.2			
104418	G2906-036S	105101	G2906-036SW	600 / 450	2040 / 1530	277 / 240	2.2/1.9			
104425	E2907-040S	105118	E2907-040SW	750	2550	120	6.3	40	8	66
104432	F2907-040S	105125	F2907-040SW	750	2550	208	3.6			
104449	H2907-040S	105132	H2907-040SW	750 / 563	2550 / 1914	240 / 208	3.1/2.7			
104456	G2907-040S	105149	G2907-040SW	750 / 563	2550 / 1914	277 / 240	2.7.2.6			
104463	E2910-048S	105156	E2910-048SW	1000	3413	120	8.3	48	10	80
104470	F2910-048S	105163	F2910-048SW	1000	3413	208	4.8			
104487	H2910-048S	105170	H2910-048SW	1000 / 750	3413 / 2550	240 / 208	4.2/3.6			
104494	G2910-048S	105187	G2910-048SW	1000 / 750	3413 / 2550	277 / 240	3.6/3.1			
104500	G2907-048S	105194	G2907-048SW	750	2550	277	3.4			
104517	E2912-060S	105200	E2912-060SW	1250	4250	120	10.4	60	12	99
103008	F2912-060S	105217	F2912-060SW	1250	4250	208	6.0			
103015	H2912-060S	105224	H2912-060SW	1250 / 938	4250 / 3189	240 / 208	5.2/4.5			
103022	G2912-060S	105231	G2912-060SW	1250 / 938	4250 / 3189	277 / 240	4.5/3.9			
103039	G2909-060S	105248	G2909-060SW	938	3189	277	3.4			
103046	E2915-072S	105255	E2915-072SW	1500	5100	120	12.5	72	14	113
103053	F2915-072S	105262	F2915-072SW	1500	5100	208	7.2			
103060	H2915-072S	105279	H2915-072SW	1500 / 1125	5100 / 3825	240 / 208	6.3/4.7			
103077	G2915-072S	105286	G2915-072SW	1500 / 1125	5100 / 3825	277 / 240	5.4/4.7			
103084	G2911-072S	105293	G2911-072SW	1125	3825	277	4.1			
103091	F2917-084S	105309	F2917-084SW	1750	5950	208	8.4	84	16	125
103107	H2917-084S	105316	H2917-084SW	1750 / 1313	5950 / 4464	240 / 208	7.3/6.3			
103114	G2917-084S	105323	G2917-084SW	1750 / 1313	5950 / 4464	277 / 240	6.3/5.5			
103121	G2913-084S	105330	G2913-084SW	1313	4464	277	4.7			
103138	F2920-096S	105347	F2920-096SW	2000	6826	208	9.6	96	18	138
103145	H2920-096S	105354	H2920-096SW	2000 / 1500	6826 / 5100	240 / 208	8.3/7.2			
103152	G2920-096S	105361	G2920-096SW	2000 / 1500	6826 / 5100	277 / 240	7.2/6.3			
103169	G2915-096S	105378	G2915-096SW	1500	5100	277	5.4			
103213	F2925-120S	105422	F2925-120SW	2500	8532	208	12.0	120	22	151
103220	H2925-120S	105439	H2925-120SW	2500 / 1875	8532 / 6375	240 / 208	10.4/9.0			
103237	G2925-120S	105446	G2925-120SW	2500 / 1875	8532 / 6375	277 / 240	9.0/7.8			
103244	G2918-120S	105453	G2918-120SW	1875	6375	277	6.8			

HIGH ALTITUDE ELECTRIC BASEBOARD CONVECTION HEATERS

FOR ALTITUDES ABOVE 6500 FEET



- Available in white with aluminum heating element and aluminum fins, Ivory models require 4 week lead time
- Painted 22ga. steel front with 20 ga. junction boxes located on each end of the heater - junction boxes contain quick connect cable clamps and 6" ground lead wires
- Over-temperature thermal limit extends entire length of heated area
- A full length wireway provided along the back of the heater - optional wireway covers are available
- Heater can be mounted to the wall by using the key hole knockouts every 4" at the back of the heater
- Optional In-Built thermostats field installed in the junction box
- HEIGHT - 6" DEPTH - 2 1/2"

UPC 686334	WHITE MODEL	WATTS	BTU's	VOLTS	AMPS	HEATER LENGTH (IN)	WT. (LBS.)	LIST
101226	E2903-024HAW	375	1275	120	3.1	24	5	57
101233	F2903-024HAW	375	1275	208	1.8			
101240	H2903-024HAW	375 / 281	1275 / 955	240 / 208	1.6/1.4			
101257	G2903-024HAW	375 / 281	1275 / 955	277 / 240	1.6/1.2			
101264	E2905-028HAW	500	1706	120	4.2	28	6	59
101271	F2905-028HAW	500	1706	208	2.4			
101288	H2905-028HAW	500 / 375	1706 / 1275	240 / 208	2.1/1.8			
101295	G2905-028HAW	500 / 375	1706 / 1275	277 / 240	1.8/1.6			
101301	E2906-036HAW	600	2040	120	5.0	36	7	65
101318	F2906-036HAW	600	2040	208	2.9			
101325	H2906-036HAW	600 / 450	2040 / 1530	240 / 208	2.5/2.2			
101332	G2906-036HAW	600 / 450	2040 / 1530	277 / 240	2.2/1.9			
101349	E2907-040HAW	750	2550	120	6.3	40	8	68
101356	F2907-040HAW	750	2550	208	3.6			
101363	H2907-040HAW	750 / 563	2550 / 1914	240 / 208	3.1/2.7			
101370	G2907-040HAW	750 / 563	2550 / 1914	277 / 240	2.7.2.6			
101387	E2910-048HAW	1000	3413	120	8.3	48	10	82
101394	F2910-048HAW	1000	3413	208	4.8			
101400	H2910-048HAW	1000 / 750	3413 / 2550	240 / 208	4.2/3.6			
101417	G2910-048HAW	1000 / 750	3413 / 2550	277 / 240	3.6/3.1			
101424	G2907-048HAW	750	2550	277	3.4			
101431	E2912-060HAW	1250	4250	120	10.4	60	12	102
101448	F2912-060HAW	1250	4250	208	6.0			
101455	H2912-060HAW	1250 / 938	4250 / 3189	240 / 208	5.2/4.5			
101462	G2912-060HAW	1250 / 938	4250 / 3189	277 / 240	4.5/3.9			
101479	G2909-060HAW	938	3189	277	3.4			
101486	E2915-072HAW	1500	5100	120	12.5	72	14	115
101493	F2915-072HAW	1500	5100	208	7.2			
101509	H2915-072HAW	1500 / 1125	5100 / 3825	240 / 208	6.3/4.7			
101516	G2915-072HAW	1500 / 1125	5100 / 3825	277 / 240	5.4/4.7			
101523	G2911-072HAW	1125	3825	277	4.1			
101578	F2920-096HAW	2000	6826	208	9.6	96	18	141
101585	H2920-096HAW	2000 / 1500	6826 / 5100	240 / 208	8.3/7.2			
101592	G2920-096HAW	2000 / 1500	6826 / 5100	277 / 240	7.2/6.3			
101608	G2915-096HAW	1500	5100	277	5.4			
101653	F2925-120HAW	2500	8532	208	12.0	120	22	156
101660	H2925-120HAW	2500 / 1875	8532 / 6375	240 / 208	10.4/9.0			
101677	G2925-120HAW	2500 / 1875	8532 / 6375	277 / 240	9.0/7.8			
101684	G2918-120HAW	1875	6375	277	6.8			

ELECTRIC BASEBOARD ACCESSORIES

IN-BUILT THERMOSTAT KITS - 50° - 90°F RANGE

IVORY & WHITE		THERMOSTAT WITH TWO COVER PLATES - ONE WHITE AND ONE IVORY	WT.	LIST
UPC 686334	MODEL NUMBER			
105460	TBS	SPST-In-Built 22A @ 120-240V 18A @ 277V	12 lbs.	34
502702	TBS-TP	SPST-In-Built 22A @ 120-240V 18A @ 277V Tamperproof	12 lbs.	
105477	TBD	DPST-In-Built 22A @ 120-240V 18A @ 277V	16 lbs.	41
502719	TBD-TP	DPST-In-Built 22A @ 120-240V 18A @ 277V Tamperproof	16 lbs.	



In-Built thermostat kits

WHITE		BRONZE		THERMOSTAT MOUNTED TO COVER PLATE	WT.	LIST
UPC 686334	MODEL NUMBER	UPC 686334	MODEL NUMBER			
115384	CTBSW	102629	CTBSB	SPST-In-Built 22A @ 120-240V 18A @ 277V	12 lbs.	44
115391	CTBDW	102636	CTBDB	DPST-In-Built 22A @ 120-240V 18A @ 277V	16 lbs.	52

FIELD INSTALLED ACCESSORIES

DESCRIPTION	IVORY		WHITE		BANKERS BRONZE		WT.	LIST
	UPC 686334	MODEL	UPC 686334	MODEL	UPC 686334	MODEL		
Disconnect Switch, 20 Amp, 120-277V	106108	DS	106115	DSW	106122	DSB	1 lb.	72
Corner Sections	105491	CS	105507	CSW	105514	CSB	1 lb.	31
1" Joiner Kits	105521	JK	105538	JKW	105545	JKB	1/4 lb.	21
6" Blank Relay Section (Relay Not Included)	105552	LVRS	105569	LVRWS	105576	LVRBS	1.5 lbs.	81
Receptacle Section (Baseboard Mounted) 15 amp 120 VAC	105583	BDR115	105590	BDR115W	105606	BDR115B	1/4 lb.	21
Receptacle Section (Mounted in 6" Blank) 15 amp 120 VAC	105613	DR115	105620	DR115W	105637	DR115B	2 lbs.	94
Transfer Switch (Mounted in 6" Blank) 16 amp 120 VAC	105644	SR120	105651	SR120W	105668	SR120B	2 lbs.	128
Transfer Switch (Mounted in 6" Blank) 16 amp 240 VAC	105675	SR220	105682	SR220W	105699	SR220B	2 lbs.	156

OPTIONAL WIREWAY COVERS*

UPC 686334	MODEL	BASEBOARD LENGTH (in.)	COVER LENGTH (in.)	WT. Lbs.	LIST
105705	WWA01	24	20	1	30
105712	WWA02	28	24	1.5	33
105729	WWA03	36	32	2	36
105736	WWA04	40	36	2.5	41
105743	WWA05	48	44	3	43
105750	WWA06	60	56	4	46
105767	WWA07	72	68	5	52
105774	WWA08	84	80	6	60
105781	WWA09	96	92	7	69
105798	WWA00	120	116	8	84

BLANK SECTIONS

LENGTH	IVORY		WHITE		BANKERS BRONZE		WT. Lbs.	IVORY WHITE LIST	BRONZE LIST
	UPC	MODEL	UPC	MODEL	UPC	MODEL			
24"	105804	BBS024A	105903	BBS024AW	106009	BBS024C	5	48	99
28"	105811	BBS028A	105910	BBS028AW	106016	BBS028C	5.5	52	108
36"	105828	BBS036A	105927	BBS036AW	106023	BBS036C	6	63	125
40"	105835	BBS040A	105934	BBS040AW	106030	BBS040C	7	68	131
48"	105842	BBS048A	105941	BBS048AW	106047	BBS048C	8	76	135
60"	105859	BBS060A	105958	BBS060AW	106054	BBS060C	10	92	187
72"	105866	BBS072A	105965	BBS072AW	106061	BBS072C	12	111	205
84"	105873	BBS084A	105972	BBS084AW	106078	BBS084C	15	116	234
96"	105880	BBS096A	105989	BBS096AW	106085	BBS096C	17	136	262
120"	105897	BBS120A	105996	BBS120AW	106092	BBS120C	20	166	330

(* Wireway Adapters are standard on Commercial BB Heaters.