




WARMPLY YOURS
MAKING COMFORT EASY

Low Voltage Floor Heating for Showers, Saunas and Spas





PROGRAMMABLE THERMOSTAT



24 VOLT WARMING ROLL



24 VOLT TRANSFORMER

Enjoy the Luxury of a Warm Shower Floor from WarmlyYours

System Description

Do you look forward to taking a long, relaxing shower... but dread stepping onto a cold tile floor? Enhance your everyday shower experience with WarmlyYours low voltage floor heating system. Bask in warm, flowing water while being enveloped by radiant heat emanating from your shower floor – the perfect formula for your shower oasis.

Safe for use in wet locations, this system is ideal for today's spa bathroom. Now, you can enjoy your bathroom floor heating experience right into your walk-in shower. Our low voltage system works especially well for larger, luxurious showers with a European curbless design. Offered in several sizes, the 24 volt warming rolls and companion transformers are available to accommodate your shower application. Simple to install over a waterproof membrane, this system is designed to warm shower floors, steam showers and saunas.

To receive a custom installation plan, simply provide your bathroom's floor plan with dimensions, and include your shower location. WarmlyYours will design your shower system and include a product recommendation for a 24 volt warming roll, transformer and programmable thermostat. For larger applications, multiple 24 volt warming rolls may be required.

24 Volt TempZone™ Warming Roll

TempZone™ floor warming systems are engineered with an insulated copper alloy resistance warming cable sewn to a fiberglass mesh backing. The warming cable is evenly spaced in 2" serpentine loops and provides 25% more heating capacity than competitive products. Measuring less than 1/8" thick, the mesh system installs easily under tile and stone and is offered in a variety of lengths to accommodate your project requirements.

TempZone™ is covered by our 10-year, NoNonsense™ Warranty.

ITEM NUMBER	WIDTH	LENGTH	SQ.FT	WATTS	AMPS
02-15B-24	1'6" (457mm)	2'2" (660mm)	3.25ft ² (0.30m ²)	49W	2.03A
03-15B-24	1'6" (457mm)	3'2" (965mm)	4.75ft ² (0.44m ²)	71W	2.97A
05-15B-24	1'6" (457mm)	5'2" (1575mm)	7.75ft ² (0.72m ²)	116W	4.84A
07-15B-24	1'6" (457mm)	7'2" (2184mm)	10.75ft ² (1.00m ²)	161W	6.72A
15-15B-24	1'6" (457mm)	15'2" (4623mm)	22.75ft ² (2.11m ²)	338W	14.08A

24 Volt Transformer

The first and only transformer specifically designed and UL listed to be mounted in any of the 6 available positions. This step-down transformer is required for operation of the 24 volt floor warming system. Offered in a range of sizes to meet your project specifications. All 24 volt transformers come with a 2-year manufacturer's warranty.

ITEM NUMBER	DIMENSION (width x length x height)	MAXIMUM ROLL	MAX WATTS	AMPS
TR-300VA-Q	8.63" (219mm) x 5.75" (146mm) x 3.1" (79mm)	20ft ² (1.86m ²)	300W	2.9A
TR-500VA-Q	11" (279mm) x 7" (178mm) x 4.5" (114mm)	33ft ² (3.07m ²)	500W	4.8A
TR-750VA-Q	11" (279mm) x 7" (178mm) x 4.5" (114mm)	50ft ² (4.65m ²)	750W	7.2A
TR-1050VA-Q	15" (381mm) x 10" (254mm) x 5.25" (133mm)	70ft ² (6.50m ²)	1050W	10.1A
TR-1500VA-Q	15" (381mm) x 10" (254mm) x 5.25" (133mm)	100ft ² (9.29m ²)	1500W	14.4A

Programmable Thermostat

The Energy Star Rated SmartStat™ thermostat has an in-floor sensor which provides accurate temperature control. The programmable function gives you the option of 4 programmable events for each day of the week, allowing you to pre-heat your shower so that it's warm and inviting any time of the day. It also features a manual set-back to a "high" or "low" temperature level. Comes equipped with a built-in GFCI and a 2-year manufacturer's warranty.